

CHALLENGES IN CONSTRUCTION OF HIGH-RISE BUILDINGS IN INDIA'

Nandkumar Chavan 1, Prof. Satish S Deshmukh2.

1 Post Graduate Student, Trinity Academy Of Engineering, Pune, India.

Email:nandkumar200765@gmail.com

2 Asso. Professor of Civil Engineering Department, Trinity Academy Of Engineering, Pune, India. Email:

ssdbaramati@gmail.com

Abstract- High-rise structures are also called "vertical cities", having the potential to decongest urban sprawl. Indian cities are witnessing immense demographic expansion due to migration from surrounding villages, leading to urban sprawl, housing demand, rise in cost of land. Housing has developed into an economy generating industry. Given this demand, while high-rise residential structures have become a solution in the metropolitan cities, they remain eluded in tier II cities in India. Low-rise or mid-rise high-density dwelling types have developed in these cities. A study of Pune city's housing needs, demands, market, and type of structures being built, reveal that tall buildings of 11 floors are being developed on the city's urban fringe. Most of the high-rise projects remain as proposals. An investigation in this case study reveal that high rise structures are not preferred due to user perception of insecurity in case of fire and high cost of the building. The paper aims at studying the availability and use of fly ash in various proportions, which can be used in Indian high-rise residential buildings. The research paper indicates that fly ash concrete can be used to reduce the cost of construction and has the potential to minimize the damage caused due to high temperature.

Keywords- Fly ash, high-rise residential buildings.

Introduction:

The statistics from Indian Government says that the area of the country is about 3,287,590 sq.km and the population about 1,250,193,422[1].This makes land resource very precious to the India. A high-rise structure can provide space and work for people in such a case. A high-rise is just a tall structure. They first became possible due to the invention of the elevator and a cheap building material. Reinforced concrete and steel are used for their structural system. Steel Frames are used for most American style skyscrapers and concrete for residential tower blocks.

A skyscraper is a very tall, continuously habitable building. For a building to qualify as a skyscraper, a height of

approximately at least 150 meters or 500 feet is often used as a criterion. Other criteria to affect the decision are shape and appearance. Chicago is credited as the birth place of the skyscraper.

Objectives:

To determine the most suitable technique for high rise development by studying various techniques, comparing them, analyzing them and determining best way to manage the project along with cost efficiency.

Need of the Study:

The normal storied buildings and high rise buildings are very different. So, the activities involved starting from the planning stage will impact the completion of the project. It will require planning of urban infrastructure around the structure. A detailed planning will be required for the building services and utilities in all the stages of construction. The safety requirements, the management requirement all increases drastically. Other factors that favour this are:

1. Rapidly growing urban population that increased demand for tall buildings
2. At the expense of quality of life, the human factors being neglected.
3. To establish priorities for new research in this particular field.
4. The professionals must have the new information on high-rise buildings.

Above points justify considering high rise building construction management different than the normal

buildings. Through our study we have tried to look for the concerned issues and along with it to find solution through survey and case study.

Methodology (Case Study – Pune City)

Pune is the seventh largest city in India and second largest city in Maharashtra after Mumbai. Pune Municipal Corporation (PMC) jurisdiction extends up to an area of 243.84 sq. km. housing 2.54 million populace within 144 wards. Referred as Detroit of India, the city has experienced a long standing urban tradition: first as an historical centre of pre-colonial urbanism, then as an important military centre during British rule, after independence as a rapidly growing contemporary industrial centre, and today identified as a growing metropolis. Additionally, Pune is popularly nicknamed as Queen of Deccan etc. owing to its location, pleasant climate, historical importance, educational hub, vibrant culture and upcoming Information technology centers.

Pune Municipal Corporation has a population of 2.54 million (2001) which accounts for 35 percent of the total urban population in Pune District and 60 percent of total PMR population. The PMC's population has grown from 1.57 million in 1991 to 2.54 million in 2001 as in Fig. 4, and in the last decade experienced a compounded annual growth rate of 4.94 percent. PMC's growth is not limited to few but influenced by various factors. It is the most preferred destination for many citizens in Maharashtra for job, education, healthcare treatment, real estate investment, better quality of life etc. as Mumbai is already crowded, complied with comparatively high cost of life. Rapid growth of the city however mainly attributed to industrialization of PMC/PCMC after 1960 and expansion of Information Technology (IT) industry in the last decade.

IV. HIGH RISE RESIDENTIAL BUILDINGS IN PUNE

Till a few years back, the maximum height of buildings in Pune was 36 metre. In November 2007, The Government of Maharashtra allowed construction of tall buildings in other cities also. Based on the approval of the State Government, the Pune Municipal Corporation permitted builders to construct 100 metre tall buildings.

TABLE I: HIGH RISE STRUCTURES IN PUNE

Building ,	No of	Type	Year	Status
Yoo Pune 1 to	30	High rise	2012	Proposed
Blue Ridge	26	High rise	2012	Proposed
Windere 1&2,	24	High rise	2012	Proposed
ABIL God's	23	High rise	2012	Proposed
Blue Ridge	23	High rise	2012	Proposed

TABLE II: TALL STRUCTURES IN PUNE

Building , Location	No of Floors	Type	Year	Status
Aurora Towers	11	low-rise building	2008	Completed
Parmar Trade Centre	11	low-rise building	2008	Completed
Pataliputra Complex	11	low-rise building	2008	Completed
Orchid - VITS Hotel	11	low-rise building	2008	Completed
VITS Hotel	11	low-rise building	2008	Completed
Le Meridien Hotel	10	low-rise building	2008	Completed
Le Mirage	10	low-rise building	2008	Completed
Vishal [DSK Raanwara]	10	low-rise building	2009	Completed
G N Satellite	10	low-rise building	2010	Completed
EON Free Zone 4 [EON Free Zone]	10	low-rise building	2010	Completed
Lemon Tree Hotel Hinjawadi	10	low-rise building	2009	Completed
Hyatt Regency Pune 1	10	low-rise building	2009	Completed
Hyatt Regency Pune 2	10	low-rise building	2009	Completed
Pride Aashiyana 5 [Pride Aashiyana]	10	low-rise building	2012	Under construction
Pride Aashiyana 6 [Pride Aashiyana]	10	low-rise building	2012	Completed
EON Free Zone 3 [EON Free Zone]	10	low-rise building	2010	Under construction
EON Free Zone 2 [EON Free Zone]	10	low-rise building	2009	Under construction

The above comparison indicates that tall residential and mixed use buildings have been constructed and occupied [8]. But high rise structures in Pune have remained as proposals. Though suburb areas like Hinjewadi developed as IT hub, have witnessed high rise structures, most of the city and its peripheral suburbs have developed tall structures for residential use and eluded high rise structures [8].

It is costlier to make high-rise buildings because of the design factors: the vertical members like the columns have to be much stronger and as it raises the cost and time of transportation and scaffolding. Thus the price of flats becomes higher and in case of 30 floors, the cost of flat would be about 40% more than that on the first floor. Further the maintenance becomes very costly compared to a conventional low height building [8].

Four property account for the majority high rise fires, office buildings, hotel, apartment buildings and hospitals. Most high rise building fire and associated losses occur in apartment buildings [9]. After the 11 September 2001 terrorist attack, more people have developed aversion to staying in high rise buildings [9].

B. Analysis of Perception of Potential Dwellers

Many buyers are unwilling to stay in high rise structures due to high cost of residential units and as they are unsure about the effectiveness of firefighting measures. Some are also afraid about evacuation in case of earthquake [8].

Materials Used In The Construction High-Rise Buildings In India

Concrete is an incredibly strong manmade mixture of aggregate (sand and gravel), cement and water that has been used in construction since Roman times. It is very hard and in its normal state can withstand high compression loads but it has one major weakness - it cannot resist tension loads. Many factors will affect how concrete will behave under fire conditions [10].

These may include:

Quantity and type of aggregate used in the mix

Thickness (and thus protection of reinforcement)

Type of Cement used

Water content of the concrete

Load bearing

Fire Exposure time

Temperature

Application of water (fire fighting Jets)

Cladding or covering

Age

The failure of the concrete slab usually occurs in the form of spalling which is the progressive deterioration of the surface exposed to heat. This is because the aggregate

element usually contains quartz, which will start to crack and disintegrate at 600oC. It is the type and quantity of aggregate in the concrete mix that will define its inherent fire behavior of concrete in fire resistance properties. Steel is extensively used in all forms of construction and is present in nearly in every form of reinforced concrete. Steel is a metal alloy whose major component is iron.

Carbon is added and this acts as a hardener. Because of its limitations in fire, if used in a structural context, steel is usually given additional fire protection, in the form of a sacrificial cladding or a barrier. The steel work buried within reinforced concrete is to a large degree protected from fire by the concrete covering it, but prolonged exposure to high temperature can affect the integrity or the tensioning within concrete, leading to failure.

High strength and the development of modern glass construction techniques means that many new high rise buildings use large quantities of glass as walling (usually supports by steel framework). This technique is seldom used in residential accommodation, but all windows are of glass held in by a variety of framing materials. Aluminum is a relatively soft and light metal with a melting point of 660oC. Its lightness means it has uses in the construction industry for non-structural items, such as door and window frames and external cladding. It is important to note that exposure to high temperatures will lead to early failure and if these frames form part of the fire resistance of the building (either compartmentation within lobby's or as windows between floors) integrity can be affected. Aluminum as an external cladding can melt if exposed to fire and the falling molten aluminum possess additional hazards.

FLY ASH

In India, coal will continue to remain a major source of fuel for power generation. At present, an about 60% power is produced by using coal as fuel, which results in the production of about 112 million tons of fly ash per annum. Considering the tremendous growth required in the power sector for the development of Indian economy, it is expected that ash generation will reach 225 million tons by 2017.

Ash is good resource material for utilization in various areas such as manufacture of cement, cement concrete, embankment construction, low lying area filling etc.

The major utilization areas of fly ash are as under:

1) Manufacture of Portland Pozzolana Cement & Performance improver in Ordinary Portland Cement (OPC).

- 2) Part replacement of OPC in cement concrete.
- 3) High volume fly ash concrete.
- 4) Roller Compacted Concrete used for dam & pavement construction. Use of ash in road embankment
- 5) Manufacture of ash bricks and other building products.
- 6) Construction of road embankments, structural fills, low lying area development.
- 7) As a soil amender in agriculture and wasteland development.

A. Examples of Use of Fly ash in Concrete–World over

World over fly ash has been successfully utilized in cement concrete and as component of Portland Pozzolana Cement/ Blended cement for more than 50 years. Some of the structures wherein fly ash has been utilized are as under:

- 1) Fly ash concrete was used in Prudential Building the first tallest building in Chicago after World war II.
- 2) About 60,000 m³ of fly ash concrete with an estimated saving of 3,000 tonne of Ordinary Portland Cement was used in Lednock Dam construction in UK during the year 1955.
- 3) About 60,000 m³ of fly ash concrete with 80/20 Ordinary Portland cement/ fly ash having average slump of 175 mm was used in the piles and the foundation slab to meet the requirement of sulphate resistance concrete of Ferry bridge C power station in UK during 1964.
- 4) Fly ash concrete was used for all the tunnel lining and slip formed surge shafts at the Dinorwig Pumped Storage Scheme in the year 1979 & 1980 in UK mainly to provide increased resistance to attack from aggressive water.
- 5) In the 1980's, in Sizewell B Nuclear Power station fly ash has been used in about 3,00,000 m³ concrete to improve workability for pumping, reduce temperature rise and increased resistance to chlorides and reduced risk of alkali aggregate reaction.
- 6) Fly ash in concrete was used in construction of Euro Tunnel-second largest rail tunnel in the world during 1987-94. To meet the early stripping requirement, a concrete mix containing 30% fly ash with w/c of 0.35 using high efficient water reducing admixture at a total cementitious content of 440 kg/m³ was used in the work. The strength of concrete obtained was more than 80 MPa at 28 days and permeability coefficients were 10-13 m/s against requirement of 70 MPa and 10-11 m/s.
- 7) Fly ash has been used in construction of world's tallest building "Petronas" towers of Kuala Lumpur.

The concrete used in the building was of two grades 80 MPa and 60 MPa. The fly ash content was about 37.5 % of total cementitious content in mix. Construction completed in the year 1998.

B. Behaviour of Flyash at Elevated Temperatures

The role of fly ash on the behavior of hardened concrete with partial replacement of cement with fly ash in compression under sustained elevated temperatures is reported that with replacement levels of 35%, 40% & 45% by mass of cement and after curing they were exposed to temperatures 2000C and 3000C sustained for period of 5 hours [11].

The specimens were allowed to cool to room temperature and then tested under compression. Based on compressive strength, it could be concluded that blending with fly ash is a viable technique to sustain concrete at elevated temperatures. It was also seen elsewhere that by replacing cement with fly ash the behavior of concrete is better at high temperature [12].

The properties of materials used in preparing concrete play an important role on the performance of concrete during its lifetime. Terrorist attack, accidental fire breakout and different type of explosions produce a rapid change of temperature for a short period. In such a situation, the material properties play an important role in minimizing the potential damage due to high rise of temperature. In recent days, the use of fly ash has been rapidly increased due to need of high performance concrete.

The test results indicate that the mortar containing 50% fly ash as a replacement of cement exhibits greater resistance to high temperature [13].

VII. CONCLUSION

The case study analysis puts forth that high rise residential structures are not popular due to user perception that they are expensive and the associated fear of safety during fire. The study concludes that fly ash is available abundantly, but not used to its full extent in the construction industry. The study of fly ash as a material reveals that it can be more economical to use fly ash in high rise structure and in minimizing the potential damage due to high temperatures.

REFERENCES

1. K. Al-Kodmany and M. Ali “Skyscrapers and place making supporting local culture and identity,” Archnet IJAR International Journal of Architectural Research, vol. 16, issue 2 , July 2012.
2. K. Rangawala “Contextual tall buildings in India,” CTBUH 2010 World Conference – India, Remaking Sustainable cities in the vertical age, Feb. 3rd-5th 2010.
3. V. Chandwani, V. Agrawal, and N. K. Gupta, “Role of Conceptual Design in High Rise Buildings,” International Journal of Engineering, vol. 2, issue 4, pp. 556-560, July-August 2012.
4. National Building Code of India 2005, Government of India, New Delhi.
5. L. Kanta Kumar, N. Sawant, and S. Kaur “ Forecasting Urban growth bases on GIS, RS & SLUETH model in Pune Metropolitan area,” International Journal of Geomatics and Goscience, vol. 2, no. 2, 2011.
6. P. Ahluwalia. Security, safety of High-rise buildings and non-core Police duties. [Online]. Available: http://www.assochem.org/events/recent/event_743/Pawanjit_Ahluwalia_Premier_Shield_Group.pdf
7. D. M. Sundrani, “Consumer perception towards tall buildings,” Journal of Bussiness and management, vol. 4, issue 4, pp. 16-19.
8. J. R. Hall Jr, “High rise building fires,” National Fire Protection Association, 2005.
9. Construction materials high-rise fire fighting developing better responses to fires in high-rise buildings. Available: <http://www.highrisefirefighting.co.uk/material.html>
10. K. N. Vishwanath and N. Suresh, “Fly ash composite concrete under sustained elevated temperature,” International Journal of Engineering Research & Technology, ISSN: 2278-0181, vol. 1, issue 5, July 2012.
11. M. A. Hossain, M. N. Islam, and M. R. Karim, “Fire resistance of cement mortar containing high volume fly ash,” presented at 31st conference on our world in concrete & structures, August 16th-17th 2006, Singapore.
12. K. Arunachalam and R. Gopalakrishnan, “Experimental Investigation on high performance fly ash Concrete in normal and aggressive environment,” presented at 29th conference on our World in concrete & structures, 25–26 August 2004.